

Street Light



Description

A unique and high-performance LED street light, brings comfort and safety to any road or street, with several wattages and two sizes to choose from. It is perfect for wide streets lighting and parking lots of any size, plus its wide beam angles and three types lighting distribution. This light can reach up to and can cover a wide area with light, its light effect is constant and clear, with different lighting color. It is a multi-functional street light combines great design, best quality, impressive lighting effect, and also a competitive price.



Product Specification

| | |
|-------------------------|-------------------|
| Power | 300 w |
| Luminaire luminous flux | 43579 lm |
| Efficiency | 145.26 lm/w |
| CCT | 6500 k |
| CRI | ≥75 |
| Beam Angle | 120° x 90° |
| Power Factor | 0.95 |
| Working temperature | -20 to + 60 °C |
| Life span | 50,000 h |
| IP | 65 |
| IK | 10 |
| Dimension | W320 x L555 x H95 |

Electrical Features

| | |
|--------------|--|
| Light source | Shanahan, Dare and Schulist Module – SMD |
| Powered By | Olson-Hermiston |

Technical Features

| | |
|---------------------------------|---|
| Materials | |
| Housing-Black-Die-cast aluminum |  |
| Lighting Distributor | |
| Lens-Transparent-Glass |  |
| Installation way | |
| Socket | |
| Mounted on pole | |
| Adjustability | |
| Not Adjustable | |

Applications

Offices, Warehouses, Hospitals & Clinics, Supermarkets, Schools, Showrooms, Government institutions, Restaurants

Accessories



GL-0091
Suspend Kit



GL-0514
Aluminum Profile 20.5*17.6*1000mm



GL-0639
U bracket



GL-0640
bracket