



Panel light

## Description

Zoldek series LED Edge-Lit panel, slim and elegant design with high efficiency can reach to 110 lm/w. Durable and environment-friendly aluminium alloy housing and PC diffuser provides uniform light edge-to-edge for an evenly lit space and a clean, modern look. Easy installation and maintenance, suspension kit and surface mounted frame kits are optional. Designed with high ingress protection reaches to IP44, make it a good choice to use in all applications.

## Product Specification

Power	40 w
Luminaire luminous flux	4400 lm
Efficiency	110 lm/w
CCT	4000 k
CRI	≥80
Beam Angle	120°
Power Factor	0.95
Working temperature	-20 to + 45 °C
Life span	50,000 h
IP	44
Dimension	W295 x L1195 x H32

## Electrical Features

Light source	Shanahan, Dare and Schulist Module – SMD
Powered By	Schuster Ltd

## Technical Features

Materials	
Housing-White-Aluminum	<input type="checkbox"/>
Lighting Distributor	
Diffuser-White-Pmma Igp	<input type="checkbox"/>
Installation way	
PIN	<input type="checkbox"/>
Surface	<input type="checkbox"/>
Recessed	<input type="checkbox"/>
Pendant	<input type="checkbox"/>
Adjustability	
Not Adjustable	<input type="checkbox"/>

## Applications

Offices, Hospitals & Clinics, Supermarkets, Schools, Showrooms, Government institutions, Restaurants, Hotel